



Easyway International, LLC

**11331 East 183rd St. #210
Cerritos, CA 90703**

Application Protocol for Easyway Products

Easyway Tile and Grout Cleaner (Blue Label)

1. Apply the product to the mineral or organic (scum) build up. Dip brush to the product and keep doing it as the build up normally neutralizes the product. (Optional: You may lower the water level as low as you want)
2. Keep doing it all throughout the swimming pool tiles.
3. Rinse tile with water or wet rag
4. Dry tile and you will see that it is clean.

Easyway Premera Multi-Purpose Sealer H1 (Water Base)

1. Check swimming pool tiles and grout if they are really clean before sealing. Once sealed it will be so hard to take away the sealed dirt.
2. Shake well the sealer while it is still in the gallon to mix the molecules that settled in the bottom of the gallon.
3. Put product into a spray bottle or hudson sprayer. Spray it directly to the pool tiles and grout. You may use paint roller to roll it in or use rag wet with product and rub it in.
4. Air dry, it normally takes 15-20 minutes dry time depending on the existing temperature. When its dry the surface is sealed. The longer cure time the more the sealer gets more durable.

Easyway Premera Glass Sealer H2 Hydrophobic (Water Base)

1. Check swimming pool glass tiles if they are really clean before sealing. Once sealed it will be so hard to take away the sealed dirt.
2. Shake well the sealer while it is still in the gallon to mix the molecules that settled in the bottom of the gallon.

3. Put product into a spray bottle or soak regular rag with H2 glass sealer and rub it in. Spray it directly to the pool glass tiles. You may use paint roller to roll it in or use rag wet with product and rub it in.
4. Wait at least 45 seconds and wipe it with micro fiber rag (very important). After wiping wait at least 1 minute and the surface is sealed.
5. The longer the surface is cured the more durable it becomes.

Easyway Descaler (Red Label) For Pool Maintenance / Primary Cleaner

1. For build up that is just about to come out again, usually still not so stubborn build-up, you can do the process interval every 3-4 weeks, if water is so hard (many minerals) you may do it once a week or twice a week depending on your assessment.
2. Dilute product 1 part chemical to 5 parts water. One quart product can go as much as 1 gallon of water diluted.
3. Put diluted product into a bucket, get rag or sponge dip into product and start wiping it directly to the swimming pool tiles. Though sometimes you will not see the build up with your naked eye but it is already starting to building up that is why it is important to stay on top of it.
4. After wiping product into the pool tiles, grout or any surface that you applied the product on make sure to rinse it with water or wet rag.
5. **After rinsing with water or wet rag** it's your option if you want to wipe it dry or not.
6. You may use the Easyway Descaler as well as the primary product for initial application.

Note: Please make sure you are wearing the proper PPE for your full protection:

Prepared by:

Jonan Baladjay
Robin Baladjay
Easyway International, LLC